

Sonitrol's Indoor/Outdoor Standard Dome Camera




High resolution day or night

- Sonitrol offers a high-resolution camera with Sony® technology that can be used in a majority of indoor & outdoor applications
- The varifocal lens gives you flexibility to adjust the “field of view” to get the perfect picture. It is also tri-axis so it can easily mount on a ceiling or a wall.
- The day/night capability enables the camera to see during the day in full color and in lower light conditions in black & white

Model	Sonitrol Dome Camera	Comments
Part	SONCAM-FLEX	Sonitrol part number
Image Device	1/3" Interline Sony® Super HAD CCD	Sony ® technology for quality & reliability
Picture Element	768 (H) X 494 (V)	Excellent image quality
Resolution (color)	550 TVL	High Resolution (it is over 480TVL)
Minimum Illumination	True Day/Night - .1 lux color; .002 lux B&W	Able to see in full color and in lower light conditions
Signal to Noise	>50dB	Minimal signal noise
Optical	Lens: 3.3 - 12mm; Varifocal; auto iris	Can manually zoom from wide angle to telephoto
Backlight Compensation	Yes - center window; off selectable	Filters out sharp background lighting
White Balance	Auto sensing	Can compensate for indoor/outdoor lighting
Auto Gain Control	Auto	Automatically adjusts for low light conditions
Synchronization	Internal	Allows to sync multi-cameras to DVR/monitor
Dome Construction	Indoor/Outdoor; Aluminum; Vandal resistant	Vandal and weather resistant features
Mounting	Wall or ceiling; flush / surface mount incl	Can be installed as flush or surface mount
Power	DC 12V OR AC 24V	Works with multiple input power types
Temperature	14° to 113° F	Wide range of optimal operating temperatures
Dimensions	5.63" X 3.94"	Device Size

Indoor field of view



Lens Range: Sign is 60 feet away



3 mm



12 mm